



All-purpose pistol-grip screwdriver with positive action offers full torque throughout rundown.

- ◆ Convenient one-handed operation with forward and reverse control at trigger.
- ◆ Variable speed throttle for easy starts.
- ◆ Through-handle exhaust directs air away from work area.
- ◆ Compact, lightweight and maneuverable.

Specifications at 6.2 bar (90 PSI)

Part number
Ordering number
Bit holder size (hex)
Clutch type

LA412-EU
0133007
1/4 in
Positive Jaw Clutch

PERFORMANCE

Rated power
Maximum working torque
Maximum free speed

0.33 hp / 0.25 kW
9.6 ft-lb / 13 Nm
1 800 rpm

AIR SYSTEM

Air inlet (NPTF)
Minimum hose size
Average air consumption
Air consumption at free speed
Air consumption at load

1/4 in
3/8 in / 10 mm
3 cfm / 85 l/min
4 cfm / 113 l/min
29 cfm / 821 l/min

NOISE & VIBRATIONS

Sound pressure / power
Vibration level (ISO8662)

89.6 / 102.6 dB(A)
0.8 m/s²

WEIGHT & DIMENSIONS

Tool weight
Tool dimensions (l x w x h)
Shipping weight
Shipping dimensions (l x w x h)
UPC/EAN Code

2.53 lb / 1.15 kg
172 x 42 x 150 mm
2.95 lb / 1.34 kg
172 x 220 x 55 mm
6 63023 00978 0