



Tool features adjustable clutch for sensitive control. The best for all screw sizes where torque control is important. Not recommended where the tapping torque exceeds the final torque.

- ◆ Variable speed throttle for easy starts.
- ◆ Rear exhaust.
- ◆ Compact, lightweight and maneuverable.

Specifications at 6.2 bar (90 PSI)

Part number	LA413-EU
Ordering number	01330109
Bit holder size (hex)	1/4 in
Clutch type	Adjustable Cushion Clutch

PERFORMANCE

Rated power	0.33 hp / 0.25 kW
Maximum working torque	9.6 ft-lb / 13 Nm
Maximum free speed	1 800 rpm

AIR SYSTEM

Air inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	3 cfm / 85 l/min
Air consumption at free speed	4 cfm / 113 l/min
Air consumption at load	27 cfm / 481 l/min

NOISE & VIBRATIONS

Sound pressure / power	88.5 / 101.5 dB(A)
Vibration level (ISO8662)	1.1 m/s ²

WEIGHT & DIMENSIONS

Tool weight	2.60 lb / 1.18 kg
Tool dimensions (l x w x h)	260 x 42 x 42 mm
Shipping weight	3.15 lb / XXX kg
Shipping dimensions (l x w x h)	75 x 295 x 55 mm
UPC/EAN Code	6 63023 00981 0