

Air Drills

NEW

7804XP

- 6.5 mm (1/4 in).
- 0.12 kW (0.17 HP).
- 1 600 rpm.
- Only 0.6 kg and 180 mm.
- Composite housing.
- Reversible.



7807R-EU

- 10 mm (3/8 in) standard chuck.
- 0.25 kW (0.33 HP) – 2 000 rpm.
- Reversible.

7803AKC



7803A - Standard chuck

7803AKC - Keyless chuck

7803RA - Standard chuck, reversible

7803RAKC - Keyless chuck, reversible

- 13 mm (1/2 in) chuck.
- 0.37 kW (0.50 HP) – 500 rpm.

Accessories: **7803-BOOT** (CPN: 45524287), protective tool boot.

LA410-EU

- 10 mm (3/8 in) standard chuck.
- 0.25 kW (0.33 HP) – 4 500 rpm.

Accessories: **327LS-K284** (CPN: 10323095), piped-away exhaust system.

7802A

Standard chuck

7802AKC

Keyless chuck

7802RA - Standard chuck, reversible

7802RAKC - Keyless chuck, reversible

- 10 mm (3/8 in) chuck.
- 0.37 kW (0.50 HP) – 2 000 rpm.

Accessories: **7802-BOOT** (CPN: 45524279), protective tool boot.



LA410-EU

Specifications at 6.2 bar (90 psi)

	CPN	Max. Ø mm	Max. Nm	Max. kW	1 min. rpm	kg	L mm	AIR NPTF	AIR mm	L/s	Max. L/s	dB(A)	m/s ² / K ⁽¹⁾
Air Drills													
7803A	80113632	13	28	0.37	500	1.63	195	1/4"	10	1.9	12.7	83.0	<2.5
7803AKC	10563724	13	28	0.37	500	1.63	200	1/4"	10	1.9	12.7	83.0	<2.5
7803RA	80113673	13	28	0.37	500	1.64	195	1/4"	10	1.9	12.7	83.0	<2.5
7803RAKC	10563732	13	28	0.37	500	1.64	200	1/4"	10	1.9	12.7	83.0	<2.5
7802A	80113616	10	7	0.37	2 000	1.31	163	1/4"	10	1.9	12.3	83.0	2.8 / 0.7
7802AKC	10563716	10	7	0.37	2 000	1.35	175	1/4"	10	1.9	12.3	83.0	2.8 / 0.7
7802RA	80113640	10	7	0.37	2 000	1.30	163	1/4"	10	1.9	12.3	83.0	2.8 / 0.7
7802RAKC	80147424	10	7	0.37	2 000	1.36	175	1/4"	10	1.9	12.3	83.0	2.8 / 0.7
7807R-EU	01352160	10	5	0.25	1 800	1.07	206	1/4"	10	1.9	8.1	89.2	<2.5
LA410-EU	01328616	10	2	0.25	4 500	0.91	228	1/4"	10	1.4	12.8	84.9	2.9 / 0.7
7804XP	16599433	6.5	3	0.12	1 600	0.80	180	1/4"	10	0.9	8.3	83.6	3.0 / 0.8

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty.

Air Tyre Buffers

327LS

- 0.38 kW (0.50 HP).
- 3 000 rpm.
- Only 0.50 kg.
- Piped-away exhaust system.



22 000 rpm



327-EU

- Standard chuck: 10 mm (3/8 in).
- 0.38 kW (0.50 HP).
- Only 0.73 kg.

Accessories: **327LS-K284** (CPN: 10323095), piped-away exhaust system.

Specifications at 6.2 bar (90 psi)

	CPN		 kW	 rpm	 kg	 mm	 NPTF	 mm	 L/s	 L/s	 dB(A)	 m/s ² / K(°)
Air Tyre Buffers												
327LS	01371699	7/16"⌀	0.38	3 000	0.50	216	1/4"	10	6.6	12.6	77.4 (2)	<2.5
327-EU	01343771	10 mm	0.38	22 000	0.73	224	1/4"	10	7.1	12.6	87.9	4.6 / 1.1

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty — (2) Piped-away exhaust system.