



2131PEX

1/2" ATEX impact wrench

ATEX 2014/34/EU
Ex h IIA T6 Gb X



Reliability: Ingersoll Rand Twin Hammer impact mechanism.
Pressure-fed mechanism lubrication

Control: feather-touch trigger allows precise delivery of power and speed.

Specifications at 6.2 bar (90 psi)

Part Number **2131PEX**

PERFORMANCE

Recommended Torque range **68-542Nm**

Max Torque **813Nm**

AIR SYSTEM

Air Inlet (NPT) **1/4"**

Air consumption at load **11 L/s**

WEIGHT & DIMENSIONS

Tool weight **2,0 kg**

Origin **Made in USA**

2925RBP1TiEX

3/4" ATEX Titanium impact Wrench

ATEX 2014/34/EU
Ex h IIA T6 Gb X



The 2925 Series comes with an unbeatable feature list which meets the most demanding requirements for enhanced performance and unbeatable durability in super heavy industrial applications.

Performance: Ingersoll Rand Twin Hammer impact mechanism.

Durability: Titanium hammer case is lightweight with unparalleled durability. Corrode-X™-corrosion resistant treatment on internal parts guards against contaminants in the air system.

Adaptability: the motor can be easily converted to provide maximum torque in forward direction for fastening applications.

Specifications at 6.2 bar (90 psi)

Part Number **2925RBP1TiEX**

PERFORMANCE

Recommended Torque range **407-1288Nm**

Max Torque **2169Nm**

AIR SYSTEM

Air Inlet (NPT) **3/8"**

Air consumption at load **28 L/s**

WEIGHT & DIMENSIONS

Tool weight **5,44 kg**

Origin **Made in USA**

- **Titanium hammer case** is lightweight with unparalleled durability
- **Corrode-X™**-corrosion resistant treatment on internal parts guards against contaminants in the air system.

3940B2TiEX

1" ATEX Titanium impact Wrench

ATEX 2014/34/EU
Ex h IIA T6 Gb X



The revolutionary design of the 3900 Series gives more power and greater durability than any competitive model. From the inside out, the comprehensive list of features and benefits makes it the only choice for professionals in the oil and gas, power generation and other demanding industries.

Performance: 6780 Nm (5 000 ft-lb) of maximum torque in reverse. Twin Hammer impact mechanism. High-performance motor package includes 7-vane rotor and bronze end-plates – can be easily converted to provide maximum torque in forward direction for fastening applications.

Durability: lightweight titanium hammer case with unparalleled durability. Corrosion- and wear-resistant bronze end-plates.

Specifications at 6.2 bar (90 psi)

Part Number **3940B2TiEX**

PERFORMANCE

Recommended Torque range **6678-2237Nm**

Max Torque **3729Nm**

AIR SYSTEM

Air Inlet (NPT) **1/2"**

Air consumption at load **35 L/s**

WEIGHT & DIMENSIONS

Tool weight **6,6 kg**

Origin **Made in USA**

- ***Titanium hammer case*** is lightweight with unparalleled durability
- ***Corrode-X™***-corrosion resistant treatment on internal parts guards against contaminants in the air system.

3942B2TiEX

1" ATEX Titanium impact Wrench

ATEX 2014/34/EU
Ex h IIA T6 Gb X



The revolutionary design of the 3900 Series gives more power and greater durability than any competitive model. From the inside out, the comprehensive list of features and benefits makes it the only choice for professionals in the oil and gas, power generation and other demanding industries.

Performance: 6780 Nm (5 000 ft-lb) of maximum torque in reverse. Twin Hammer impact mechanism. High-performance motor package includes 7-vane rotor and bronze end-plates – can be easily converted to provide maximum torque in forward direction for fastening applications.

Durability: lightweight titanium hammer case with unparalleled durability. Corrosion- and wear-resistant bronze end-plates.

Specifications at 6.2 bar (90 psi)

Part Number **3942B2TiEX**

PERFORMANCE

Recommended Torque range **1356-2644Nm**

Max Torque **4407Nm**

AIR SYSTEM

Air Inlet (NPT) **1/2"**

Air consumption at load **44 L/s**

WEIGHT & DIMENSIONS

Tool weight **10,5 kg**

Origin **Made in USA**

- **Titanium hammer case** is lightweight with unparalleled durability
- **Corrode-X™**-corrosion resistant treatment on internal parts guards against contaminants in the air system.

3955B2TiEX

1,5" ATEX Titanium impact Wrench

ATEX 2014/34/EU
Ex h IIA T6 Gb X



The revolutionary design of the 3900 Series gives more power and greater durability than any competitive model. From the inside out, the comprehensive list of features and benefits makes it the only choice for professionals in the oil and gas, power generation and other demanding industries.

Performance: 6780 Nm (5 000 ft-lb) of maximum torque in reverse. Twin Hammer impact mechanism. High-performance motor package includes 7-vane rotor and bronze end-plates – can be easily converted to provide maximum torque in forward direction for fastening applications.

Durability: lightweight titanium hammer case with unparalleled durability. Corrosion- and wear-resistant bronze end-plates.

Specifications at 6.2 bar (90 psi)

Part Number **3955B2TiEX**

PERFORMANCE

Recommended Torque range **2170-5290Nm**

Max Torque **6780Nm**

AIR SYSTEM

Air Inlet (NPT) **1/2"**

Air consumption at load **37 L/s**

WEIGHT & DIMENSIONS

Tool weight **15,7 kg**

Origin **Made in USA**

- **Titanium hammer case** is lightweight with unparalleled durability
- **Corrode-X™**-corrosion resistant treatment on internal parts guards against contaminants in the air system.



7803RAKCEX

1/2" ATEX reversible drill

ATEX 2014/34/EU
Ex h IIA T6 Gb X



7803 Series

7803 Series If you need more power in your drill turn to Ingersoll Rand's line of high quality 1/2" (13 mm) drills

500 RPM and deliver 0.50 hp (0.38 kW)

Features

- Powerful 0.5 hp (0.38 kW) motor
- Variable speed throttle
- Reversible motor models available
- Composite, keyless chuck models available
- Keyless Chuck

Specifications at 6.2 bar (90 psi)

Part Number 7803RAKCEX

PERFORMANCE

Max free speed rpm **500**

Power **0,5HP (0,38Kw)**

13mm chuck

AIR SYSTEM

Air Inlet (NPT) **1/4"**

WEIGHT & DIMENSIONS

Tool weight **1,67 kg**

Length mm **200**

Origin **Made in USA**

7802RAKCEX

3/8" ATEX reversible drill

ATEX 2014/34/EU
Ex h IIA T6 Gb X



7802 Series

7802 Series Ingersoll Rand 3/8" Chuck (10 mm) drills feature a quiet design, reversible and keyless chuck model.

Features

- Powerful 0.5 hp (0.38 kW) motor
- Variable speed throttle
- Reversible motor models available
- Composite, keyless chuck models available
- Keyless Chuck

Specifications at 6.2 bar (90 psi)

Part Number 7802RAKCEX

PERFORMANCE

Max free speed rpm **2000**

Power **0,5HP (0,38Kw)**

10 mm chuck

AIR SYSTEM

Air Inlet (NPT) **1/4"**

WEIGHT & DIMENSIONS

Tool weight **1,67 kg**

Length mm **175**

Origin **Made in USA**